



MIG-21 IloT Gateway

The MIG-21 is the most cost effective gateway that provides easy way of connecting Modbus serial devices to MQTT server via cellular network, truly a plug and play solution for connecting Industrial devices to IloT system, it is a compact protocol converter cum gateway that converts Modbus serial data to MQTT IloT data.

The MIG-21 can be remotely configured via it's web server and can be easily set up to read serial devices like Drives, PLC, IO modules, HMI, etc., the MQTT publishing interval is programmable.

The MIG-21 allows a fast and easy access to the IloT world and is compatible with all IloT servers that supports MQTT protocol. It provides encrypted communication using TLS / SSL protocols, ensuring a secure and safe communication.

The MIG-21 is simple to install and easy to manage and having an integrated web server to allow the user to configure the device parameters (MQTT, Ethernet, Modbus).

Features

- 4G Modem (LTE Cat1) optional
 - Support frequency band :
GSM : 900/1800MHz
LTE FDD : B1/B3/B5/B7/B8/B20/B28/B31/B72
 - LTE Cat1: 10 Mbps (DL) 5 Mbps (UL)
- 2G Modem optional
 - Supported freq. bands: 850/900/1800/1900MHz
 - Up-link/down-link up to 85.6Kbps
- Remotely monitoring data on MQTT server
- Retains the data in-case of network failure
- Embedded web server for easy configuration
- DHCP / Static IP support
- Configurable RS485 baud rate, parity and stop bit
- Completely isolated in both RS485 and RJ45
- One touch recovery (Factory reset configuration)
- LED indication for easy setup and trouble shooting
- Selectable publishing interval for data publish to MQTT server (1 minute to 1440 minutes)
- Support up to 16 Modbus slave devices or 128 Modbus read register (max.)
- DIN rail mounting option

Applications

- Energy management system
- Building management system
- Remote data acquisition for MODBUS client devices
- Automatic meter reading

TECHNICAL SPECIFICATIONS

Network	4G (LTE Cat 1)/2G	Digital Input Specification	
SIM Slot	Micro SIM (3FF)	No of Channels	2
Antenna Connector	1 x (SMA female)	Input Frequency	1KHz max
Ethernet	1 x RJ45 (10/100Mbps)	Pulse Width	500 uSec
Serial Port 1	1 x RS485	Mode of Operation	Normal (ON/OFF) / counter
	Baud rate : 9600/19200/38400/57600/115200, 2 Pin plugging screw terminal	Counter Resolution	32 Bit
Input/Output	2 x Digital input	Input Voltage Range	+24V DC (±10%) Ext. power supply
	2 x Digital output	Input Impedance	5100 Ω
Memory Size	4 MBytes (for data logging)	Digital Output Specification	
RTC with Battery Back Up	Yes	No of Channels	2
CPU	ARM cortex-M4 core, 192MHz	Output Type	Open collector (Sink type) (external +24V DC required)
Input Voltage Range	9 to 36VDC, <5W	Default/Predefined Value	ON/ OFF
Power Connector	2 Pin plugging screw terminal	Pulse Width	10mSec
LED Indicators	Power, TX (RS485), RX (RS485)	Maximum Current	100mA per output
	RSSI, network and status LEDs	Mode of Operation	Discrete (ON/ OFF), Impulse mode
SMS Features	Yes	Vce ON	1.1V max
Enclosure Dimension	111mm(W) x 75mm(H) x 25mm(D)	Isolation	
Ingress Protection	IP20	Supply to RS485	1500VAC RMS
Enclosure Material	ABS	Supply to Ethernet	1000VAC RMS
Enclosure Mounting	DIN rail	Supply to Digital Input	1500VAC RMS
Weight	140 gms approx.	Supply to Digital Output	1500VAC RMS
Enclosure Color	Black		
Operating Temperature	0 °C to +55 °C		
Humidity	20 to 90 % RH (Non-condensing)		

Ordering Code for MIG-21

Model	Mounting	Cellular Type	Input Type	Output Type
MIG-21	X	X	X	X
	D	1	N	N
		2	1	1