



CDU

Clean Room Display Unit

Masibus model CDU Clean Room Display Unit is designed to measure and display temperature, humidity and differential pressure in one compact enclosure.

CDU Clean Room Display Unit accepts analog input from temperature, humidity and differential pressure sensors, optionally the sensors for all 3 parameters are integrated inside for ease of use & installation. CDU is also available in remote sensor with 10 meter cable option for RH + T measurement

CDU is available in two display options either 4 digit 0.56" red seven segment displays to indicate temperature, %RH and DP individually or 3.5" TFT LCD, CDU with LED display option has individual LEDs for status indication for all three channels. High and low alarm LED indications are settable using programming modes. One no potential free digital input for door status available in CDU with LCD option.

CDU has inbuilt buzzer for audible process value violation. Data acquisition can be done on SCADA/ PLC application through RS-485 using Modbus protocol.

CDU-LED version optionally also accepts humidity and temperature input through wireless zigbee network from Masibus make HT16Ew humidity & temperature transmitter.

Designed using proven micro-controller technology, this clean room display unit has been validated to perform accurate and reliable performance in harsh field environment.

Features

- RH, Temperature and DP measurement
- Advanced digital RH+T sensor technology
- Calibration not required for digital RH+T sensor
- Internal sensor option (Ease of installation)
- Remote sensor option for RH+T measurement
- Available in LED and touchscreen TFT LCD display options
- 3 programmable alarms with visual annunciation
- Software programmable channel ranges, units & input types
- Real time clock with battery back-up
- Synchronized with server clock over RS485
- Data backfilling via DNP 3.0 avoiding data loss (optional)
- RS485/MODBUS RTU multidrop communication for PLC, SCADA etc.
- FDA 21 CFR part11 compliant SCADA version also Datalogging
- Optional Wireless connectivity available in LED version (with HT16Ew model)
- Touch Sensitive keypad for CDU-XP
- CDU-XP is suitable for gas group IIA and IIB, Zone 1&2 and IP55 as per IS/IES 60529-2001

Applications

- Pharmaceutical industry
- HVAC (Heating, ventilation, air conditioning, cooling)
- Blood stations, pharmacies
- Horticultural and cultivation of plants
- Pharma Environments monitoring applications
- Data acquisition, analysis and processing

TECHNICAL SPECIFICATIONS

Input				Output			
Input Sensor Type				RTC		Real time clock with battery backup	
Input Type	Differential Pressure (DP)	Humidity (RH)	Temperature (T)	Buzzer		In built buzzer provided to beep during set values violated condition	
Integral	✓	✓	✓	Loop Power Supply		24VDC (±10%) @75mA with In built short circuit protection (For Analog I/P)	
Analog (4-20mA/ 0-10VDC)	✓	✓	✓	Communication			
Remote Sensor with Cable	✗	✓	✓	Interface		RS-485 (2 Wire)	
Wireless	✗	✓	✓	Protocol		Modbus-RTU, DNP 3.0 (Optional)	
Measurement Range				Baud Rate		9600, 19200, 38400 bps	
Integral [▲]	±125 Pa, ±500Pa, ±1000 Pa 0-125 Pa, 0-500Pa, 0-1000 Pa	0-100%RH	0 to 60°C	Data Backfilling		Yes (with DNP 3.0 protocol only)	
Analog	-999 to 999			Wireless (Optional)*			
Wireless	NA	0-100%RH	0 to 60°C	Frequency Band		ISM 2.4 GHz	
Accuracy [▲]				Protocol		ZigBee (IEEE 802.15.4 standard)	
Integral	± 2% of FS (Unidirectional)	±2.5% (0 to 90% RH) ±3.5% (90 to 100% RH)	±0.4°C	Transmit Power		63mW (+18 dBm)	
Analog	0.1% of full span + 1 count			Receiver Sensitivity		-101 dBm	
Repeatability	✗	0.25%	0.24°C	Connectivity		With HT16Ew (Data received from RH + T)	
Hysteresis	✗	0.8%	✗	Antenna		Internal	
Resolution				Data Logging			
Integral	0.1/1 (user selectable)	1%	0.1 °C	Memory		64 Mbits	
Analog	1 count	1 count	± 0.1 °C	Record Type		Date/ Time/ Temperature/ Humidity/ Pressure/ Alarm status	
Response Time				Total Records		Up to 400000	
Integral	2 Sec.	12 Sec typically		Record Transmit Interval		User selectable from every 1 Min to 9999 Min	
Analog	<1 sec.			Power Supply			
Analog Input type Features				Voltage		18-36V DC	
ADC Resolution	16 Bit			Power Consumption		<5VA	
NMRR	>40dB			Data Backup		Non-volatile memory (Can be written up to 100000 times)	
CMRR	>120dB			Isolation (Withstanding voltage)			
Temp. Co	<100 ppm/°C			• Between primary terminals* and secondary terminals**: At least 1500V AC for 1 minute			
Input Impedance	>1 MΩ for Voltage i/p; 250Ω for mA i/p			• Between secondary terminals**: At least 500V AC for 1 minute			
Max. Voltage	20V DC			• Insulation resistance: 20MΩ or more at 500V DC between power terminals and grounding terminal			
Display & Keys				• * Primary terminals indicate power terminals.			
LED Display				• **Secondary terminals indicate I/O signal & communication O/P.			
LCD Display				Physical			
Process Value	3-line (RH+T+DP), 0.56" 4-digit 7 segment red LED		3.5" TFT LCD, 262k color graphical with white backlight, 320 x 480 pixels, Visual area: 49.96 x 74.44 mm	CDU		CDU-XP	
	0.56" 4-digit 7 segment red LED (Optional)		3.5" TFT LCD	Enclosure Dimension (in mm)	150 x 150 x 50 (H x W x D) for LED 163 x 174 x 50 (H x W x D) for LCD Tolerance: ±2mm	212.20(H)x 212.20(W)x 55(D) Tolerance: ±2 mm	
	9 Red LED's for alarm, batch and communication		Unit symbol display through soft input	Stainless Steel Front Plate	165 x 165 (H x W) mm (LED) 195 x 195 (H x W) mm (LCD)	250(H) x 260(W)	
	Menu, Increment, Decrement, Acknowledgement		Capacitive touch panel	Weight Approx.	<1 kg	<4 kg	
RTC	0.56" 4-digit 7 segment red LED (Optional)		3.5" TFT LCD	Enclosure Material	Enclosure M.S. powder Coated Body with Stainless Steel Front Flush	Die cast aluminium alloy LM6	
Status Indication	9 Red LED's for alarm, batch and communication		Unit symbol display through soft input	Enclosure Protection	IP20	IP55	
Keys	Menu, Increment, Decrement, Acknowledgement		Capacitive touch panel	Terminal Cable Size	1.5mm ²	1.5mm ²	
Environmental				Cut Out in mm	150(H) x 150(W) for LED 163(H) x 174(W) for LCD	225(H) x 225(W)	
Ambient Temperature				0 to 55°C			
Storage Temperature				0 to 80°C			
Humidity				20% to 95% RH (Non-Condensing)			
Instrument Warm-up Time				Approx. 15 minutes			

Ordering Code																
Model	No of Parameter		No of Integral Sensor		Input Type				RTC display		Power supply		Communication Protocol		Display Type	
CDU	X		X		XXX	DP [▲]	RH	T	X		X		X		X	
CDU-XP**	1	1 Parameter	0	None	I00	Integral sensor	None	None	Y	Yes	U2	18-36V DC	M	Modbus	LED	7 Seg LED
	2	2 Parameter	1	One	OII	None	Integral sensor	Integral sensor	N	No			D	DNP 3.0	LCD	TFT LCD
	3	3 Parameter	2	Two	III	Integral sensor	Integral sensor	Integral sensor								
			3	Three	AAA	Analog I/P	Analog I/P	Analog I/P			*Available in LED version only. Works only with Masibus wireless transmitter HT16Ew #Remote Sensor shall be supplied with 10 meters cable ▲Please provide the measurement range for Integral DP type while ordering △Clean Air Environment **Available in LED version only.					
					ICC	Integral sensor	Remote sensor with cable	Remote sensor with cable								
					OCC	None	Remote sensor with cable#	Remote sensor with cable#								
					IWW	Integral sensor	Wireless I/P*	Wireless I/P*								
					OWW	None	Wireless I/P*	Wireless I/P*								