



9000L

Signal Isolator

Single/Dual Output

Advanced. Isolated. Reliable

Masibus 9000L Signal Isolator is compact yet rugged 4 wire Isolator used for reliable isolation and attenuation of Industry Standard Field Signals. 9000L is available in Single or Dual output models.

9000L has higher noise rejection ratio that ensures accurate and noise free signal conditioning. Its Compact DIN rail mount design occupies less space and reduces cost of overall installation.

With Dual output option this model also acts as Signal distributor. A typical application could be where the signal has to be distributed for indication on local panel, field control room, main control room or DCS system. The Isolator provides a good protection for sensitive system parts against voltage spikes etc.

An exceptional feature of advanced extended universal power supply for the range of 20V to 265V DC or AC makes 9000L suitable for most of the power supply range available in field thus providing easy installation.

Masibus' 9000L Model offers a good accuracy and stability for reliable operation in hostile environments and full isolation safely separates input channel, each output channel and the power supply.

Features

- Compact DIN rail mount Design of 35mm for Single and Dual output
- Rugged & accurate 4 wire isolator
- Extended Universal Power Supply range: 20V to 265V DC or AC
- 1.5 KV AC three port isolation
- Up to 2 outputs with short circuit Protection
- High CMRR and NMRR
- High output load driving capability
- Wide span adjustment limits
- Front calibration facility via multitrurn trimpot

Applications

- Field Interface device
- Isolation of field signals
- Distribution of signals
- Translation of signals
- Factory automation
- SCADA
- DCS
- Impedance matching of transmitters and receiver instruments
- Variable Frequency Drives

TECHNICAL SPECIFICATIONS

Input			Power Supply	
	9000L	9000L-M	Voltage	20 to 265V DC/ AC, 45H z-65H z
Input type	Current	Voltage/ Current	Power Consumption	Less than 5VA
Input Range	4 to 20mA	4 to 20mA 0 to 10V DC	Power ON status LED	Red
Input Impedance	≤100 Ω	Current i/p ≤100 Ω Voltage i/p ≥1 MΩ	Isolation (Withstanding Voltage) Between primary terminals* and secondary terminals**: At least 1.5 KV AC for 1 minute Between primary terminals* and Grounding Terminal: At Least 1.5 KV AC for 1 minute Between grounding terminal and secondary terminals**: At least 1.5 KV AC for 1 minute Between secondary terminals**: At least 1.5 KV AC for 1 minute * Primary terminals indicate power terminals. ** Secondary terminals indicate I/O terminals. Insultation Resistance: > 20MΩ@500V DC between All terminals and grounding terminal.	
Temperature Coefficient	≤100 ppm/°C			
CMRR	> 100 d B			
NMRR	> 70 dB			
Output				
	9000L	9000L-M		
Output Type	Current	Voltage/ Current		
Output Range	4 to 20mA	4 to 20mA 0 to 10V DC		
Output Load Resistance	≤750 Ω	Current o/p ≤750 Ω Voltage o/p ≥2 KΩ		
Accuracy	± 0.25% of FS			
Response time	≤ 50ms			
Output Loop status LED	Green	Not available		
			Physical	
			Mounting Type	DIN Rail (35 mm)
			Terminal Block	UL,CSA standard
			Terminal Cable Size	2.5mm ²
			Enclosure Material	ABS
			IP Rating	IP20
			Dimension (in mm)	75(H) x 35.1(W) x 107.25(D)
			Weight	SOP model: 120 gms Approx DOP model: 150 gms Approx
			Environmental	
			Operating Temperature	0 to 55 °C
			Relative Humidity	30 to 95% RH (Non-Condensing)
			Protection	Conformal Coating on PCB

Ordering Code

Model	No of O/P	
9000L	X	
	1	One
	2	Two

Model		Input Type		O/P type-1		O/P type-2	
9000L	M	X		X		X	
		C	4-20mA	1	4-20mA	0	None
		G	0-10V DC	5	0-10V DC	1	4-20mA
						5	0-10V DC